




THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF EEM IT SHALL NOT BE USED, REPRODUCED OR DISCLOSED TO OTHERS IN WHOLE OR IN PART WITHOUT THE PERMISSION OF EEM. ANY MANUAL ALTERATION WITHOUT AUTHORISED SIGNATURE SHALL AUTOMATICALLY RENDER THIS DRAWING INVALID

ISSUE	DESCRIPTION	DATE	SIG

DOUBLE INLET



Impeller	:M.S Powder Coated
Rotor	:Aluminium Casting, Powder Coated in Black
Casting	:Aluminium Die Casted
Insulation	:F
Class	
Bearings	:Ball Bearing
Direction	:Clockwise
of Rotation	
Duty Cycle	:SI



MODEL	EDB 150 150 S2	EDB 150 150 T2
Volts	230	415
Hz	50	50
Amps	1.70	0.60
Watts	460	400
Airflow (M³/hr)	1200	1200
RPM	2600	2600
Capacitor Mfd	12.5	-
dB(A)	76	76
Weight Kgs	8.5	8.5
Perm-amb temp °C	60	60


Motor insulation: Class F
List of Routine Tests conducted.
1. Measurement of Winding Resistance.
2. Measurement of parameter like, Input power, Current, speed and vibration at
3. Withstand voltage test at 2200V(30), 1500V(10)
4. Insulation Resistance Test 500V(10)
The minimum insulation resistance shall be 5MΩ.

Note:
*All Dimensions in mm
*Design specifications and technical characteristics are subject to change without notice.
*Air output and pressure data are provided for Reference only
*Air output-Conversion to cfm : multiply "m³/hr" by 0.59
*Due to continuous development, We reserve the right to modify the above details and specification without prior notice



DRG NO. EEM J 23-09

PL NO. NIL



SCALE
NTS

DOUBLE INLET
MODEL EDB 150 150 S2/T2

	NAME	SIGNATURE	DATE
DRN	JSV		18-10-2023
CHKD	PSP		18-10-2023
APPD	EKD		18-10-2023

EYYANI ELECTRIC MACHINES PVT.LTD
BANGALORE 560 058
www.eyyani.com
e-mail: info@eyyani.com