



THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF EEM IT SHALL NOT BE USED,REPRODUCED OR DISCLOSED TO OTHERS IN WHOLE OR IN PART WITHOUT THE PERMISSION F EEM. ANY MANUAL ALTERATION WITHOUT AUTHORISED SIGNATURE SHALL AUTOMATICALLY RENDER THIS DRAWING INVALID

ISSUE	DESCRIPTION	DATE	SIG

SINGLE INLET


Impeller Rotor	M.S Powder Coated Aluminium Casting, Powder Coated in Black
Casting Insulation Class	Aluminium Die Casted "F"
Bearings	Ball Bearing
Direction of Rotation	Clockwise
Duty Cycle	SI



MODEL	ESB 120-30 S2
POLES	2
VOLTAGE (VAC)	230
CURRENT (A)	0.15
POWER (W)	50
SPEED (RPM)	2600
AIRFLOW (M³/hr)	140
AIRFLOW (CFM)	82
NOISE dBA	72
CAPACITOR uf	2
WEIGHT Kg	2
TEMP (°C)	60

Motor insulation:Class F
List of Routine Tests conducted.
1.Measurement of Winding Resistance.
2.Measurement of parameter like,Input power,Current, speed and vibration at
3.Withstand voltage test at 2200V(30),1500V(10)
4.Insulation Resistance Test 500V(10)
The minimum insulation resistance shall be 5MΩ .

Note:
*All Dimensions in mm
*Design specifications and technical characteristics are subject to change without notice.
*Air output and pressure data are provided for Reference only
*Air output-Conversion to cfm : divide "m³/hr" by 1.7
*Due to continuous development. We reserve the right to modify the above details and specification without prior notice

	DRG NO.EEM J 23-001			SCALE NTS	SINGLE INLET Model ESB 120-30 S2
	PL NO. NIL				
		NAME	SIGNATURE	DATE	EYYANI ELECTRIC MACHINES PVT.LTD BANGALORE 560 058 www.eyyani.com e-mail:Info@eyyani.com
	DRN	JSV		17-07-2023	
	CHKD	PSP		17-07-2023	
APPD	EKD		17-07-2023		