



THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF EEM IT SHALL NOT BE USED,REPRODUCED OR DISCLOSED TO OTHERS IN WHOLE OR IN PART WITHOUT THE PERMISSION F EEM. ANY MANUAL ALTERATION WITHOUT AUTHORISED SIGNATURE SHALL AUTOMATICALLY RENDER THIS DRAWING INVALID

SINGLE INLET



Impeller Rotor :M.S Powder Coated
:Aluminium Casting, Powder Coated in Black
Casting :Aluminium Die Casted
Insulation :“F”
Class
Bearings :Ball Bearing
Direction of Rotation :Clockwise
Duty Cycle :SI



MODEL	ESB 200 100 S4	ESB 200 100 T4
POLES	4	4
VOLTAGE (VAC)	230	415
CURRENT (A)	0.8	0.3
POWER (W)	175	160
SPEED (RPM)	1365	1350
AIRFLOW (M³/hr)	1370	1370
AIRFLOW (CFM)	794	794
NOISE dBA	68	68
CAPACITOR µf	6	-
WEIGHT Kg	8.3	8.3
TEMP (°C)	60	60


Motor Insulation:Class F
List of Routine Tests conducted.
1.Measurement of Winding Resistance.
2.Measurement of parameter like,Input power,Current, speed and vibration at
3.Withstand voltage test at 2200V(30),1500V(10)
4.Insulation Resistance Test 500V(10)
The minimum insulation resistance shall be 5MΩ .

Note:
*All Dimensions in mm
*Design specifications and technical characteristics are subject to change without notice.
*Air output and pressure data are provided for Reference only
*Air output-Conversion to cfm : divide“m³/hr” by 1.7
*Due to continuous development, We reserve the right to modify the above details and specification without prior notice



DRG NO.EEM J 23-011

PL NO. NIL



SCALE
NTS

SINGLE INLET
Model ESB 200-100 S4/T4

	NAME	SIGNATURE	DATE
DRN	JSV		17-07-2023
CHKD	PSP		17-07-2023
APPD	EKD		17-07-2023

EYYANI ELECTRIC MACHINES PVT.LTD
BANGALORE 560 058
www.eyyani.com
e-mail:Info@eyyani.com